



FORKS: Forks are made from 1¼ x 4 heat treated alloy steel. Standard length is 46". Standard carriage width is 29 inches. Fork spacing is adjustable. Other fork lengths and carriage widths are available on special order.

MAST TYPE: Single stage lift.

COUNTERWEIGHT: About 1100 pounds should be added to the front of most tractors to effectively counterbalance a 2500 pound load.

SIDESHIFT (Optional): Three inches each side of mast center. Weight — 153 pounds.

HOLDDOWN: Available as an optional attachment.

MODEL NUMBER	TF6860	TF6872	TF6884	TF6896	TF68108	TF68120	TF68144
A — Lifting Capacity — Pounds at 24 Inches	2500						
B — Overall Length with Sideshift	Tractor Length Plus 18 Inches Tractor Length Plus 21 Inches						
C — Rear Mount Reach with Sideshift	29" to 37"						
Front Mount Reach with Sideshift	32" to 40"						
	18"						
	21"						
D — Overall Height Mast Lowered	52"	58"	64"	70"	76"	82"	94"
E — Overall Height Mast Raised	82"	94"	106"	118"	130"	142"	166"
F — Maximum Lifting Height	60"	72"	84"	96"	108"	120"	144"
H — Degrees Tilt Forward	6° to 10°						
J — Degrees Tilt Rearward	10° to 15°						
K — Ground Clearance	6½" to 15"						
Approximate Shipping Weight — Pounds	1132	1159	1186	1213	1240	1267	1321

* Depending on tractor tire size.

HYDRAULIC SYSTEM REQUIREMENTS: Can be operated from most tractor hydraulic systems.

Specifications and design subject to change without notice.